

Lembar data produk

Spesifikasi



APC Smart-UPS On-Line,
15kVA/15kW, Rack/Tower,
230V/380V...415V, Hard wire 5-
wire(3P+N+E)+3-wire(1P+N+E),
Network Card, W/O rail kit

SRTG15KXLI

Main

Main Input Voltage	380...415 V 230 V
Other Input Voltage	220...240 V
Main Output Voltage	380...415 V 230 V
Other Output Voltage	230 V
Rated power in W	15000 W
Rated power in VA	15000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1 Hard wire 3-wire (1P + N + E) 1 IDC connector 3-wire (1P + N + E) 1
Number of rack unit	7U
Battery type	Lead-acid battery
Provided equipment	Smart UPS signalling RS-232 cable

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Number of battery replacement quantity	2
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery voltage	+/- 192 V
Battery charger power	2160 W rated
Battery power in VAh	3366 VAh capacity 3366 VAh runtime
Battery life	3...5 year(s)
Replacement battery	APCRBC172
Battery option	SRTG192XLBP2 1 6912 VAh SRTG192XLBP2 2 9953 VAh SRTG192XLBP2 3 13824 VAh SRTG192XLBP2 4 17606 VAh
Extended runtime	1

General

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

Physical

Colour Black

Height 30.6 cm

Width 440 mm

Depth 70.0 cm

Product weight 142.5 kg

Mounting location Front

Mounting preference Lower

Mounting mode Rack-mounted

Two post mountable 0

USB compatible No

Input

Network frequency 40...70 Hz auto-sensing

Number of input connectors 1 hard wire 5 wire (3P + N + E)
1 hard wire 3-wire (1P + N + E)

Input voltage limits 160...285 V
380 V

Maximum input current 66 A

Switching current capacity 100 A

Input harmonic distortion Less than 5 % for full load

Input current 66 A (1 phase)
66 A (3 phases)

Load power factor From 0.9 leading to 1 lagging

Output

Maximum configurable power in W 15000 W

Harmonic distortion Less than 5 %

Output frequency 50/60 Hz +/- 0.1 Hz sync to mains

Crest factor 3 : 1

UPS type Double conversion online

Wave type Sine wave

Output overload operation 60 seconds at 125% and 30 seconds at 150%

Bypass type Built-in static bypass

Efficiency 93 % (in battery operation)

Full load runtime 00:05:30 15000 W

Half load runtime 00:14:30 7500 W

Maximum configurable power in VA	15000 VA
----------------------------------	----------

Conformance

Product certifications	CB
------------------------	----

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...3000 m
--------------------	------------

Ambient air temperature for storage	-15...45 °C
-------------------------------------	-------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Storage altitude	0...15000 m
------------------	-------------

Acoustic level	58 dBA
----------------	--------

Heat dissipation	2866 Btu/h
------------------	------------

IP degree of protection	IP20
-------------------------	------

Communications & Management

Free slots	0
------------	---

Preinstalled device	Network management card
---------------------	-------------------------

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

Emergency power off	Yes
---------------------	-----

Surge Protection and Filtering

Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
-------------------	--

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	535 mm
------------------	--------

Package 1 Width	790 mm
-----------------	--------

Package 1 Length	590 mm
------------------	--------

Package 1 Weight	157.2 kg
------------------	----------

Offer Sustainability

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Under investigation
-------------------	---------------------

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Circularity Profile	End of Life Information
---------------------	---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery

Penggantian yang disarankan